



Wisconsin Kenworth M451
580 Potts Ave

Schneider Finance, Inc.
911 Glory Road

Green Bay, Wisconsin United States 54304
Phone:
Fax:
Email:

Green Bay, Wisconsin United States 54304
Phone: (920) 499-0000
Fax:
Contact Email: kleiserd@schneider.com
Prepared for: Dan Kleiser

Vehicle Summary

	Unit		Chassis	
Model:	T680 Series Conventional		Fr Axle Load (lbs):	13200
Type:	TRACTOR		Rr Axle Load (lbs)	40000
Description:	469679		G.C.W. (lbs):	80000
	Application		Road Conditions:	
Intended Serv.:	Linehaul. Vehicles (trucks or tractors) used in		Class A (Highway)	90
Commodity:	General freight		Class B (Hwy/Mtn)	10
	Body		Class C (Off-Hwy)	00
Type:			Class D (Off-Road)	00
Length (ft):	0.0		Maximum Grade:	6
Height (ft):	0.0		Wheelbase (in):	234
Max Laden Weight (lbs):	0		Overhang (in):	62
	Trailer		Fr Axle to BOC (in):	74
No. of Trailer Axles:	2		Cab to Axle (in):	160
Type:	Dry van		Cab to EOF (in):	222
Length (ft):	53.0		Overall Comb. Length (in):	0
Height (ft):	13.5			
Kingpin Inset (in):	36		Special Req.	
Corner Radius (in):	2		U.S. Domestic Registry, 50-State	
	Restrictions			
Length (ft):	120			
Width (in):	102			
Height (ft):	13.5			

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Wisconsin Kenworth M451
580 Potts Ave

Schneider Finance, Inc.
911 Glory Road

Green Bay, Wisconsin United States 54304
Phone:
Fax:
Email:

Green Bay, Wisconsin United States 54304
Phone: (920) 499-0000
Fax:
Contact Email: kleiserd@schneider.com
Prepared for: Dan Kleiser

Data	Code	Description	\$ List	Weight
Model				
0000610	O	T680 Series Conventional Primarily for On-highway tractor applications, it features superior aerodynamics, excellent forward lighting and advanced ergonomics. Elastomer bushed front spring pins & heavy-duty shock absorber brackets. 16mm fasteners from rear cab support to end-of-frame, except tractor taper crossmember. Three vinyl inside sunvisors for LH, RH, and center. Under-dash center console with (2) cup holders, (2) 12V outlets & a storage compartment. Glove box door with locking latch.	153,588	15,075
0070043	O	T680	0	0
0080066	O	CARB Idle Emissions Reduction Feature. Paccar MX engines - Low NOx Idle.	100	0
0090076	O	76 in. Aerodyne Sleeper w/rear axle capacity less than 59,000 lb.	0	0
0091090	O	General freight	0	0
0093000	O	Linehaul. Vehicles (trucks or tractors) used in over-the-road freight hauling. Pickup to delivery distance is typically over 300 miles, & annual mileage is typically over 60,000 miles per year. Operation is typically on-highway. Road usage: minimum 1% Class B, do not code for Class D.	0	0
0096080	O	Dry van Include beverage trailer, curtain trailer, and chip trailer	0	0
0098025	O	U.S. Domestic Registry, 50-State	0	0
Engine & Equipment				
0700655	S	PACCAR MX-13 455 2013+ 455@1700 1650@1000 with engine brake. N09020 N170 120..Standard Maximum Speed Limit [LSL] N09030 N169 0....VSL Expiration Distance N09040 N162 80...Maximum Accelerator Pedal Vehicle Speed N09060 N163 0....Maximum Cycle Distance N09070 N052 650..Engine Idle Speed N09100 N015 NO...Enable Retarder During Manual Transmission Gear Selection N09110 N019 0....Delay in Engine Brake Activation w/ Brake Pedal Depressed N09120 N014 2....Auto Retard Vehicle Speed Offset N09130 N013 4....Downhill Speed Limiter Vehicle Speed Offset N09140 N006 80...Max Cruise Speed N09150 N001 16...Minimum Speed to Turn Cruise Control Off	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
N09160	N003	19...Minimum Cruise Control Speed		
N09170	N002	19...Min Speed to Automatically Turn Cruise Control On		
N09180	N005	1...Value to Increase Speed w/ Set/Accel Bump Switch		
N09190	N004	1...Value to Reduce Speed w/ Resume/Decel Bump Switch		
N09200	N039	ON...Allow Multi-Torque Only When Cruise is Active		
N09210	N193	0...EIST Expiration Distance		
N09220	N188	5...Timer Setting Non-PTO Mode w/o Park Brake Set		
N09230	N187	5...Timer Setting Non-PTO Mode w/ Park Brake Set		
N09240	N194	60...Timer for Impending Shutdown Warning		
N09250	N190	YES..Reset EIST Timer Based on Engine Load		
N09260	N191	NO...Override EIST Timer Based on Engine Load - No Shutdown		
N09270	N183	35...Engine Load Threshold		
N09280	N186	5...Timer Setting When in PTO Mode		
N09290	N200	YES..Allow EIST Timer Overrides in PTO Mode		
N09300	N185	40...Low Ambient Temperature Override		
N09310	N184	80...High Ambient Temperature Override		
N09350	N197	YES..Enable Accelerator Pedal Reset		
N09360	N199	YES..Enable Clutch Pedal Reset		
N09370	N198	YES..Enable Service Brake Reset		
N09380	N071	ON...FIC Enable/Disable		
N09390	N072	1900.Maximum Fast Idle Control Engine Speed		
N09400	N105	100..Decrease Engine Speed w/ Res/Decel Bump Switch		
N09410	N107	100..Increase Engine Speed w/ Set/Accel Bump Switch		
N09420	N104	250..Rate to Decrease Engine Speed w/ Res/Decel Switch Held		
N09430	N103	350..Rate to Increase Engine Speed w/ Set/Accel Switch Held		
N09440	N080	0...PTO Vehicle Speed Limit		
N09450	N078	ON...PTO Mode Disabled w/ Clutch Pedal Depressed		
N09460	N101	ON...PTO Mode Disabled w/ Service Brake Depressed		
N09470	N079	ON...PTO Mode Enable Only w/ Parking Brake Set		
N09480	N089	ON...PTO Mode Enable Only w/ Transmission Neutral		
N09490	N082	50...Reduce Engine Speed w/ Resume/Decel Switch Bump		
N09500	N083	50...Increase Engine Speed w/ Set/Accel Switch Bump		
N09510	N084	250..Rate of Decrease in Engine Speed w/ Switch Held Down		
N09520	N085	350..Rate of Increase in Engine Speed w/ Switch Held Down		
N09530	N110	ON...Enable Set Point w/ Set/Accel Switch Bump		
N09540	N087	780..RPM Set Point		
N09550	N086	2000.Maximum Engine Speed During PTO Operation		
N09560	N090	50...Reduce Engine Spd w/ Remote Res/Decel Switch Bump		
N09570	N092	50...Increase Engine Spd w/ Remote Set/Accel Switch Bump		
N09580	N091	200..Rate of Decrease in Engine Speed w/ Switch Held Down		
N09590	N093	250..Rate of Increase in Engine Speed w/ Switch Held Down		
N09600	N106	660..Minimum Engine Speed During PTO Operation		

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
		N09610 N077 1902.Maximum Engine Torque During PTO Operation		
		N09620 N109 NO...Enable PTO Speed Maxium Rate of Change		
		N09630 N081 75...PTO Speed Maximum Rate of Change		
		N09640 N173 0....Reserve Speed Offset		
		N09820 N065 5....HEST Warning Minimum Vehicle Speed		
		N09840 N179 YES..Enable Park Brake Reset		
		N09860 N161 120..Maximum Vehicle Speed		
		N09880 N164 474..Reserve Speed Function Reset Distance		
		N09900 N182 30...Coolant Temperature Overrule		
		N09920 N073 Trq..Cab Accel Pedal Type in PTO Mode		
		N09940 N055 780..RPM Set Point 1		
		N09960 N056 1030.RPM Set Point 2		
1000005	O	U.S. EPA Certified SmartWay Tractor. The SmartWay Transport Partnership is a collaborative voluntary program between the EPA and the freight industry. SmartWay eligible tractors offer a full aerodynamic package including integrated roof fairings, fuel tank side fairings, tractor mounted gap reducers, aerodynamic bumpers, aerodynamic mirrors, and low rolling resistance tires. Tractors meeting the basic specs can be designated and labeled with the U.S. EPA Certified SmartWay logo. The logo is located on the driver and passenger door pad map pocket. SmartWay certification requires specific tire treads. Refer to Data Book Addendum Section 12.3 for treads available.	0	0
1000153	U	Prospector version 34.0	0	0
1000155	O	Prospector version 35.0 Supersedes 34.0	0	0
1000206	O	Engine monitoring protection -Shutdown- PACCAR MX engine parameter.	0	0
1000243	O	Gearing Analysis: Performance power before economy results.	0	0
1000275	O	Customer's Typical Operating Spd: 75 MPH	0	0
1000282	O	MX Retarder State Cruise Control On Manual Mode Selecting this code will program the engine controller to make manual mode available when cruise control is on, but not set, and the engine brake switch is on. Manual mode means the engine retarder activates whenever the throttle pedal is not depressed. 2013+	0	0
1000285	O	Enable MX Retarder Auto-Retard Selecting this code will program the engine to utilize the auto retard mode whenever cruise control speed has been set and the engine brake switch is on. The auto-retard mode will control the vehicle speed to an offset from the cruise control set speed via the engine retarder. The offset speed shall be dependent upon customer inputs via the electronic programming work screen. 2013+	0	0
1000613	O	Enable Reserve Speed Drive Cycle Limit	0	0
1000683	O	Effective VSL Setting 65.0 MPH (USA)	0	0
1000858	O	Engine Idle Shutdown Timer Disabled	0	0
1000870	O	Eff EIST 0 Expiration Miles (USA) Use only with MX and Cummins engines	0	0

**Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
1006002	S	Air compressor: WABCO 28 CFM PACCAR MX.	0	0
1051200	S	Air Cleaner: composite firewall mounted PACCAR or Cummins engines	0	0
1107130	O	Fan Hub: Borg Warner On/Off MX-13	39	0
1123555	S	Cooling module: 1330 square inches. On-off fan hub, nylon fan blade, translucent top tank, air-to-air heat exchanger/aftercooler, silicone hoses w/constant torque clamps, long life coolant.	0	0
1247185	S	RH under fairing SCR w/ RH horizontal tailpipe below rail.	0	0
1324389	U	Davco Fuel Pro 382 W/120V PREHTR and	520	0
1504005	O	Immersion block heater 120V 1500W w/plug under door on T700, C500, T660, T800 & W900.	96	2
1816260	S	Alternator: PACCAR 160 amp, brush type	0	0
1821215	O	Batteries: 4 PACCAR GP31 threaded post (700) 2800 CCA dual purpose.	174	57
1836100	S	Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
1840065	S	12V low voltage disconnect for starter battery protection.	0	0
1900996	O	Jump start terminals under hood.	203	12

Transmission & Clutch

2058444	O	Transmission: Fuller RTLO16913A 13-speed w/oil cooler & pump. Standard with synthetic lubricant. Includes severe- duty pilot bearing on all class 8 models.	1,946	229
2250630	O	Clutch: Eaton 15-1/2 in Solo Advantage 1650 lb-ft Eaton 15-1/2 in Ceramic. 4 paddle self adjusting. Clutch brake. Severe duty pilot bearing. Synthetic lubrication for Eaton Fuller transmission & axles. Extended grease fit.	220	2
2294080	S	Air-assisted Hydraulic Clutch	0	0
2405405	O	Driveline: 2 heavy-duty 1 centerbearing.	646	99
2460042	O	14 in. Eaton Fuller high capacity oil to water cooler standard for transmission 1550-2250 lb-ft, 18-speed AutoShift.	0	0
2493009	O	Aluminum clutch housing	0	0

Front Axle & Equipment

2502321	O	Dana Spicer E-1322I Front Axle rated 13.2K 3-1/2in. drop.	430	33
2601605	O	Front Brakes: 13.2K Bendix RSD HP-ES S-Cam 16.5x5 in. drum brake.	-320	-49
2690002	O	Front Brake Drums: 14.6K 16.5x5 in. cast.	-143	88

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
2701300	S	Front Hub: aluminum hub pilot 13,200 lbs. 10-Bolt, 11-1/4 in. bolt circle .	0	0
2741970	S	ConMet PreSet Plus Hub package; front axle.	0	0
2750001	S	Hubcap: front vented.	0	0
2765001	O	Front Auto Slack Adjuster.	0	0
2864012	O	Front Springs: Taperleaf 13.2K w/ shock absorbers w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins. Not available on W900L.	27	9
2895221	S	Single power steering gear: 13.2K Sheppard HD94.	0	0

Rear Axle & Equipment

3124400	S	Dual Dana Spicer DSP40 rear axle rated at 40K. w/ 9.5mm housing and 1.88in. shaft diameter. Tandem rear axles.	0	0
3200336	O	Rear Axle Ratio - 3.36.	0	0
3304012	O	Rear Brakes, Bendix RSD-Compliant HP-ES S-Cam 16.5x7 in. tandem axle drum brake, Max GAWR 46k.	4	2
3392005	S	Dual Rear Brake Drums: cast.	0	0
3407050	S	Dual Rear Hubs: Aluminum hub pilot 46K 11-1/4 in. bolt circle.	0	0
3441972	S	ConMet PreSet Plus Hub package; dual rear axle.	0	0
3465002	S	Dual Rear axle automatic slack adjusters.	0	0
3485207	O	Spring Brake: 3030 long stroke dual 30 square inches travel; replaces standard 2-1/2 in. travel. Helps keep brakes in adjustment longer.	27	0
3495229	O	Bendix 4S/4M anti-lock brake system w/ air traction control (ATC) & electronic stability program (ESP) for tractor.	2,216	11
3495332	O	Bendix Wingman Advanced ACB without Side Object Detection System	3,337	22
3730026	O	Rear suspension: Tandem Kenworth Airglide 400L 40K. 54 in. axle spacing. Air suspension w/ 8.5 in. ride height. Includes single leveling valve. Includes air suspension dump valve.	1,396	-224

Tires & Wheels

4038803	O	Front tires: Goodyear G399A LHS Fuel Max 295/75R 22.5 16PR. 40.2 in. diameter, 18.8 in. SLR. Smartway certified.	-19	-6
4238855	O	Rear tires: Goodyear G572A LHD Fuel Max 295/75R 22.5 14PR. 41.1 in. diameter, drive. 19.3 in. SLR. Smartway certified. Smartway certified. Code is priced per pair of tires.	236	128
4900008	O	Rear Tire Quantity: 8	0	0
5045186	O	Front wheel: Kenworth 7-spoke 88768 22.5x8.25 aluminum with Lvl One [TM] finish, hub pilot mount. 7300lb. maximum rating. Level 1 finish. Air disc brake compatible.	439	-42

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
5245186	O	Rear wheel: Kenworth 7-spoke 88768 22.5x8.25 aluminum with Lvl One [TM] finish, hub pilot mount. 7300 lb. maximum rating. Air disc brake compatible. Code is priced per pair of wheels. Level 1 finish.	1,756	-168
5900008	O	Rear Wheel/Rim Quantity: 8	0	0
Frame & Equipment				
6054400	O	Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 285 in. to 336 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80, RBM is 1,776,000 in-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	179	218
6308710	O	Bumper: Aerodynamic, Painted. Requires a bumper setting code.	0	0
6319504	S	50.4 in. Bumper setting. Requires a bumper code.	0	0
6390103	S	Front mudflaps.	0	0
6391050	O	Custom Frame Layout: 50 or more chassis	20	0
6405045	S	T6/T7 Battery box module: Short length, aluminum parallel, w/ polymer cover. Located LH under cab behind the chassis fairing. For use only w/ 2010 SCR style exhaust.	0	0
6409901	O	Battery box location: LH Side.	0	0
6410010	O	Frame access grabhandle(s) LH mounted. Placement and quantity of grabhandles may vary due to FMCSR frame access requirements.	52	0
6414003	O	Medium aluminum frame access deck plate, 36 in.	190	15
6418006	O	Frame access steps: 2 ladder-type, LH mount. Available when rear of tank extends less than 24 in. behind rear of cab, sleeper, or side extender.	148	15
6419555	O	Partial chassis fairings w/o rearmost section: w/o LH and RH frame access. Includes DEF access cutout.	1,492	59
6451037	O	Cab side skirt: Supports on RH side.	0	55
6593071	O	Fifth Wheel: Air, Jost JSK37USB-A8PX12 12.0 in. slide, 7.75 in. height. Outboard mounting angles, 50K vertical rating, retractable LH handle. Air slide control valve standard in dash. Accommodates a 2 in. SAE kingpin. Requires some style of trailer connections.	2,217	524
6679813	U	2013 EPA Emissions Diesel Engine.	0	0
6680000	O	FW rear/fixed setting ahd of bogie 0 in indicates rearmost setting measured forward from centerline of tandem or single rear axle	0	0
6721144	O	Rear mudflap arms: Fleetline FF30SS, tapered spring loaded & stainless steel.	189	13

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
6722000	S	Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0	0
6734005	O	Quarter Fenders: Stainless Steel w/ Painted Steel brackets, single post mounted.	262	55
6744122	O	Short Tractor Taper w/o crossmember. Non-towing end-of-frame configuration.	30	-4
6747000	O	Shortest end-of-frame cutoff with specified configuration. Selecting this code will override the overhang dimension found in the Vocational Analysis of Prospector.	0	0

Fuel Tanks & Equip

7214120	O	Fuel Tank: 120 US gallon 24.5in. aluminum BOC replace. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck.	-17	6
7216100	O	Fuel Tank: 100 US gallon 24.5in. aluminum BOC add. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck. Multiple tank installations include a fuel equalization system w/ dual draw and return lines with a splitter valve located within 6 inches behind the cab. Single draw and return is an option in some cases.	1,702	114
7722022	O	Aerodynamic round DEF tank. 21 gallons of useable volume. The tank will be located just rearward of the under cab component on the side you specified, but will not be displayed in the Prospector graphic. Required capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel re-fillings for every DEF re-filling.	219	39
7889004	O	Position fuel fill beyond rear of sleeper. May have gap between under cab components & fuel tank(s) visible on chassis w/ o full chassis fairings.	0	0
7889245	S	Anti-siphon device swaged in place. For any number of fuel tanks.	0	0
7889604	O	DEF tank location is on the LH.	0	0
7930120	O	Location: 120 gal fuel tank RH behind cab	0	0
7940100	O	Location: 100 gal fuel tank LH behind cab	0	0

Cab & Equipment

8025301	S	Cab: Stamped aluminum cab with panoramic curved glass windshield. Standard with stamped aluminum doors, heavy duty in-swinging hinges, and triple sealed doors. Manufactured using self-piercing rivets and structural adhesive. Includes LED exterior marker lights and turn signals.	0	0
8071676	O	Sleeper: Integral 76in Aerodyne with full-height roof. Includes LH and RH upper crank-out windows and lockable tool box access doors on LH and RH sides.	11,030	1,150
8080942	O	Sleeper door, LH/RH w/ sliding window.	535	19

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
8090603	O	Hood: T680 125 inch BBC with side of hood air intake.	215	10
8158011	O	Espar Airtronic D2 sleeper or bunk heater w/thermostat.	1,329	14
8178213	O	Cab/Sleeper HVAC system. Cab HVAC includes defrost, A/C, and 48,000 BTU/hr heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter for cab system & recirculation filters for cab/sleeper cabin air are standard. Sleeper HVAC includes A/C and 40,000 BTU/hr heater. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without the need for additional insulation.	0	0
8201043	O	Kenworth Smartwheel: 18 in. leather wrapped with integrated radio and cruise controls.	247	2
8201200	S	Adjustable telescoping tilt steering column.	0	0
8220106	O	Gauge: Dash mounted air filter restriction gauge.	120	0
8221136	O	Gauge: Trailer reservoir air pressure gauge.	60	0
8221137	O	Gauge: Trailer air application gauge.	45	0
8221144	O	Gauge: Air suspension pressure gauge.	84	0
8222656	O	Gauge: Engine oil temperature gauge w/integral warning light. The NavPlus unit includes a virtual engine oil temperature gauge.	28	0
8222712	O	Gauge: Fuel filter restriction gauge.	98	0
8222720	O	Gauge: Manifold pressure gauge. The NavPlus unit includes a virtual manifold pressure gauge.	26	0
8224401	O	Gauge: Ammeter gauge in addition to voltmeter. W/integral warning light.	51	0
8225658	O	Gauge: Axle oil temperature, dual-drive axle. (2 gauges) w/integral warning light.	112	0
8226660	O	Gauge: Oil temperature gauge transmission. The NavPlus unit includes a virtual transmission oil temperature gauge.	34	0
8227704	O	Gauge: One additional fuel gauge for second fuel tank, w/integral warning light.	81	0
8282007	S	Kenworth Driver Performance Center:5in Full Color high resolution Thin Film Transistor (TFT) active matrix display with advanced driver information including fuel economy performance, outside air temp, clock, odometer and trip, engine hour meter, ignition timer, engine RPM, general truck information, diagnostics, and gear display. All Highline functionality is accessed via the Kenworth MCS providing intuitive control at the driver's fingertips. Also includes Dark Cabin functionality. When activated, the only interior light that will function when a door is opened is the door courtesy lamp.	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
8282013	S	Kenworth instrumentation and control package with 9 standard easy-read gauges: includes speedometer, tachometer, fuel gauge, engine coolant temp, engine oil pressure, voltmeter, dual air pressure, and DEF gauge. All accessory controls utilize electronically activated solenoids that include advanced vehicle protection interlocks.	0	0
8300008	S	Interior color: Slate Gray	0	0
8330176	O	Interior package: Vantage Cab 76in High Roof Sleeper. Includes durable headliner and vinyl sidewalls with geometric patterned trim and anodized aluminum accents throughout. Large overdoor storage bins with doors, overhead storage cubbies, full size glove box, two center console cupholders, and large door pad map pocket. Standard LH and RH power windows, electric door locks, interior LED lighting, nighttime friendly red ambient lighting for dash and footwell, and door mounted courtesy light. Includes single 42in. liftable premium pocket coil lower bunk. Also includes four standard 12V power outlets throughout the cab and sleeper. Driver sunvisor includes strap.	2,836	30
8390634	S	Rubber floormat	0	0
8410272	O	DR Seat: GT702 HB with Cloth material. The GT702 is standard with a single air bag, scissor linkage seat suspension that incorporates seat height memory, auto-leveling valves with exit air dump, and adjustable damper. It includes a dual chamber lumbar support, 10in Fore/Aft adjustment, 5in Up/Down adjustment with protection zones, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. DR seat standard w/ dual armrests.	224	0
8460272	O	RD Seat: GT702 HB with Cloth material. The GT702 is standard with a single air bag, scissor linkage seat suspension that incorporates seat height memory, auto-leveling valves with exit air dump, and adjustable damper. It includes a dual chamber lumbar support, 10in Fore/Aft adjustment, 5in Up/Down adjustment with protection zones, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. RD seat standard w/ LH armrest.	390	20
8490187	S	Seat color: Slate Gray with Gray stitching.	0	0
8497465	O	Seat Swivel for Kenworth GT Series RD Seat	545	50
8505070	O	Drawer-style refrigerator with integral freezer compartment and LED lighting. Mounted at mid-height on driver's side of 76in Sleeper.	1,165	40
8505101	O	TV Installation Package for 76in. Aerodyne: Wall mounted, articulated arm, passenger side above table and between upper and lower storage modules. 22in. flat screen maximum.	346	4
8520018	O	Liftable lower bunk for 76 in. Aerodyne: 42 in. x 80 in. pocket coil mattress	0	0
8520984	O	Stowable upper bunk for high roof 76in. Aerodyne: 30 X 78 foam mattress. Includes upper bunk LED reading lamp and tent style bunk restraints.	1,288	66
8521000	O	EVA foam pad over mattress tray: For insulation 9/16 in. thick.	123	2

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
8570026	O	Driver Side Upper Storage Unit: Wardrobe Closet with Door and Shelf for 76in Aerodyne Sleeper.	799	56
8570031	O	Driver Side Lower Storage Compartment with open space for refrigerator. Opening is 15.5 inches wide, 20.5 inches high, and 19.3 inches deep. Use with 8505070 or 8505076.	575	40
8570034	O	Rider Side Upper Storage Unit: Open microwave compartment with tie-down, inboard facing upper compartment w/ door, aft facing open compartment, and topped with open storage compartment. *Dimensions for the microwave compartment are 19.5 inches wide by 12.5 inches high by 14 inches deep.	695	45
8570040	O	Rider Side Lower Storage Unit: Rotating table, DVD tray, and lower open storage w/ two shelves. Includes ambient lighting for table and sleeper footwell.	793	66
8601423	O	Kenworth Radio with AM/FM/WB/CD/USB, Bluetooth, and Sirius-XM Satellite	606	4
8698976	O	Base Audio System - Sleeper: High performance door and back wall speakers.	89	4
8699926	O	CB installation kit: Center mounted of header. W/header mounted quick release CB mount. One red power post & one black ground post. Includes dual antenna leads located on the mirror brackets. Includes dual antenna & separate speaker.	230	2
8700168	S	Non-self cancelling turn signal: W/column-mounted headlight dimmer switch & intermittent wiper control.	0	0
8700856	O	Provision for mounting antenna for customer- installed Qualcomm tracking system. For use with Terrestrial antenna (WIB). Day Cab Location: Centerline top of roof, BOC. Sleeper Location: Left Hand, Back-of-Sleeper.	149	0
8700867	O	Qualcomm MCP200 Prewire for Cellular Service. Includes Wiring only. Use with 8700856 for mounting bracket. Trailer Tracs (AKA Q-TRACS) wiring is standard on T680/T880 models.	1,145	4
8800402	S	Dual cab-interior grabhandles: a-pillar mounted dash-wrap and b-pillar mounted grabhandles	0	0
8829600	S	Fairing under cab w/ integral steps.	0	0
8829617	O	Side extenders: 76 inch high-roof sleeper. 5-piece set extends 19 inches from back-of-sleeper and includes 7 inch rubber trailing edge. Extender set includes lower (sleeper), upper (sleeper roof), and top (sleeper roof top) extenders.	331	28
8832113	S	Kenworth Daylite Door with standard LH/RH electric door locks and LH/RH electric window controls.	0	0
8841411	S	Single air horn under cab.	0	0
8850139	S	Convex look-down mirror. Single 11in X 6in mounted to passenger door with black housing. Non-Heated.	0	0
8850815	O	Aerodynamic hood mounted mirror: Dual 8in X 6in convex mirrors with black housings and black breakaway arms. Non-Heated. T680/T880: Use code 8850144 to delete downward looking mirror over RH door when desirable.	265	4

**Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
8865002	S	Aero Mirror: Dual Kenworth aerodynamic motorized heated mirrors, 7in X 13in with cab color mirror shell and black mirror arms. Also includes LH/RH heated 6in X 7in convex mirrors. Mirror brackets set for 8-1/2 ft load width. Mirror controls located on driver side door pad.	0	0
8879439	O	Windshield Curtain with Integrated Curtain Track and Storage at B Pillar for 76in Sleepers only. Curtain runs along perimeter of the cab so maintains full use of cab and sleeper interior space. Not available on Daycabs.	382	2
8890101	S	One-piece bonded-in windshield with curved glass. Standard.	0	0
8890876	S	Kenworth cab/sleeper air suspension.	0	0

Lights & Instruments

9010801	S	Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0	0
9027110	O	Marker Lights: Five LED rectangular, flush mount.	0	0
9030016	S	Turn Signal Lights: Flush mounted LED mounted at top of fender wheel arc	0	0
9030052	S	LED Stop,Turn,Tail:Flange Mounted With Two LED backup lights and with an LED license plate.	0	0
9052011	O	Dual Flush Floodlights: First set. Each floodlight includes one switch.	120	2
9056141	O	Dual Pedestal Floodlights: Second set. Each floodlight includes one switch.	156	2
9059920	O	Floodlight Location: Located high outboard of side extender - second set.	0	0
9059921	O	Floodlight Location: Located low - first set.	0	0
9090000	O	Daytime Running Lamps.	154	0
9090039	S	Marker Lights: Interrupter switch. Included in Turn Signal for all models except T3. The T3 switch is in the dash.	0	0

Air Equipment

9101210	S	Air Dryer: Bendix AD-IS heated.	0	0
9108001	S	Moisture ejection valve w/ pull cable drain.	0	0
9110083	O	Tractor kit: Slide bar, spring hanger & composite gladhand/light plug holder mounted on back of cab/sleeper. Air and light line connections located directly behind cab/sleeper on LH framerail. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve and tractor protection valve are standard. Air lines are detachable at one end only, light lines are detachable at both ends. Conspicuity components are standard.	690	20
9120012	O	Air and light line length 12 feet	0	0

**Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
9121047	O	Phillips 12ft straight light line w/ metal plugs & 12 in. lead. Must code for tractor kit.	8	0
9140020	S	Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0	0
9140328	O	Trailer ABS electric supply through SAE J560 7-pin connector per TMC RP137).	0	0

Extended Warranty

9200021	S	Standard Warranty.	0	0
9210210	O	Heavy-duty Emissions Surcharge \$9250.	9,250	0

Miscellaneous

	O		0	0
--	---	--	---	---

Promotions

9509643	U	EPA 2010+ ISX/MX	0	0
9509645	U	SPECIAL INVOICING - MX ENGINE	0	0
9509646	U	SPECIAL INVOICING - FCA ADJ CL8 1H2015	0	0
9509647	U	SPECIAL INVOICING - FCA ADJ CL8 2H2015	0	0

Paint

9700000	O	Paint color number.	0	0
		N97020 A - SEE PAINT NARRATIVES		
		N94500 469679-469679 AA L3262EB RADIANT FIRE PRL MET B/C		
		N94510 469680-469680 AA L6106EB CHARCOAL EFFECT		
		N94520 469681-469681 AA L1677EB AUTUMN SUNBURST		
		N94530 469682-469682 AA L3443EB BAHAMA BLUE PRL MET B/C		
		N94540 469683-469683 AA L2847EB DARK BRIGHT TEAL PRL		
		N94550 469684-469684 AA L3262EB RADIANT FIRE PRL MET B/C		
		N94560 469685-469685 AA L6106EB CHARCOAL EFFECT		
		N94570 469686-469686 AA L1677EB AUTUMN SUNBURST		
		N94580 469687-469687 AA L3443EB BAHAMA BLUE PRL MET B/C		
		N94590 469688-469688 AA L2847EB DARK BRIGHT TEAL PRL		
		N97200 FRAME SEE PAINT NARRATIVES		
		N94600 469679-469679 FR N0001EA BLACK		
		N94610 469680-469680 FR N0001EA BLACK		
		N94620 469681-469681 FR N0001EA BLACK		
		N94630 469682-469682 FR N0001EA BLACK		
		N94640 469683-469683 FR N0001EA BLACK		
		N94650 469684-469684 FR N0001EA BLACK		
		N94660 469685-469685 FR N0001EA BLACK		
		N94670 469686-469686 FR N0001EA BLACK		
		N94680 469687-469687 FR N0001EA BLACK		
		N94690 469688-469688 FR N0001EA BLACK		
		N97700 BUMPER SEE PAINT NARRATIVES		
		N94700 469679-469679 BU L3262EB RADIANT FIRE PRL MET B/C		
		N94710 469680-469680 BU L6106EB CHARCOAL EFFECT		
		N94720 469681-469681 BU L1677EB AUTUMN SUNBURST		

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00



Data	Code	Description	\$ List	Weight
N94730		469682-469682 BU L3443EB BAHAMA BLUE PRL MET B/C		
N94740		469683-469683 BU L2847EB DARK BRIGHT TEAL PRL		
N94750		469684-469684 BU L3262EB RADIANT FIRE PRL MET B/C		
N94760		469685-469685 BU L6106EB CHARCOAL EFFECT		
N94770		469686-469686 BU L1677EB AUTUMN SUNBURST		
N94780		469687-469687 BU L3443EB BAHAMA BLUE PRL MET B/C		
N94790		469688-469688 BU L2847EB DARK BRIGHT TEAL PRL		
N97800	CH	FAIRINGS SEE PAINT NARRATIVES		
N94800		469679-469679 FA L3262EB RADIANT FIRE PRL MET B/C		
N94810		469680-469680 FA L6106EB CHARCOAL EFFECT		
N94820		469681-469681 FA L1677EB AUTUMN SUNBURST		
N94830		469682-469682 FA L3443EB BAHAMA BLUE PRL MET B/C		
N94840		469683-469683 FA L2847EB DARK BRIGHT TEAL PRL		
N94850		469684-469684 FA L3262EB RADIANT FIRE PRL MET B/C		
N94860		469685-469685 FA L6106EB CHARCOAL EFFECT		
N94870		469686-469686 FA L1677EB AUTUMN SUNBURST		
N94880		469687-469687 FA L3443EB BAHAMA BLUE PRL MET B/C		
N94890		469688-469688 FA L2847EB DARK BRIGHT TEAL PRL		
9943001	O	Bumper Painted Color A	0	0
9943005	O	Chassis Fairings Painted A Color	255	0
9943419	O	Imron solid 1 color aerodyne sleeper Spec A. Will be White L0006EB if no other color specified.	0	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0	0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)	\$202,055
Freight Charge	\$2,125
Options Not Subject to Discount	\$0
Surcharges Not subject to Discount	\$9,250
Total Weight	18075

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/22/2014 4:23:49 PM	Complete	Model Number:	T680 Series Conventional
Effective Date:	Aug 1, 2014		Quote/DTPO/CO:	C2126358
Prepared by:	ID: jaybowers		Version Number:	34.00